

APPLICATION NOTES



Product Features:

- Solid State Lighting Technology to deliver just the right illumination efficiently
- Low maintenance lighting solution for those hard to reach applications
- Product degradation: 70% at 3 years/30,000 hours under 24/7 continuous operating condition
- The low cost of operating will offset the cost of capital and results much lower cost of ownership than other lighting solutions
- Available in three color temperatures:
 - 3100K – Warm White
 - 4100K – Neutral White
 - 6500K – Cool White
- Available in 12 and 24 volt versions,
- 2W/FT delivers 147 lumens/FT
- Projection angle: 120 Degree Total Angle
- Standard length: 12 inches
- Low profile light weight lighting solution
- Includes adjustable mounting brackets and hardware for 0°, 45° and 90° angle mount
- Adhesive foam pads included for flush mount option
- Weather resistant
- Power requirement: 12 and 24VDC, Constant Voltage
- Power supplies are sold separately
 - EIADT-UL-004 – USA Plug (12 Volt)
 - EIADT-VDE-004 – EURO Plug (12 Volt)
 - EIADT-UL-001 – USA Plug (24 Volt)
 - EIADT-VDE-001 – EURO Plug (24 Volt)
- RoHS compliant
- Custom Length and Configurations available



Warm, Neutral, Cool White



0°, 45° and 90° angle mount

BIVAR

4 Thomas

Irvine, CA 92618

949. 951.8808

www.bivar.com