



NOTES:

1. HOLE \varnothing .129 -.134 [3.28 - 3.40]
2. TENSILE STRENGTH: 157 LBS [700N] MIN
3. SHEAR STRENGTH: 180 LBS [800N] MIN

4 SUM OF PRIMARY GRIP AND SECONDARY GRIP MUST FALL WITHIN TOTAL GRIP RANGE FOR SPECIFIED RIVET.
 MINIMUM PRIMARY GRIP 1MM
 MINIMUM SECONDARY GRIP .85MM

5. FINISH:
 BODY: ZINC AND CLEAR CHROMATE
 MANDREL: SEE CHART

6 **Special case for SKK3025PT applications.**
 A. Minimum secondary grip may go as low as .0197 [.5].
 B. .129 -.134 [3.3 -3.4] dia. hole must be maintained.
 C. Secondary grip countersink major dia. must be reduced.
 D. Potential for blind side protrusion to occur.

PATENT PENDING

P/N	"L" in. [mm]	TOTAL GRIP RANGE in [mm]	MANDREL COLOR
SKK3025PT	.091 [2.30]	.059 - .079 [1.5 - 2.0]	BLACK
SKK3030PT	.110 [2.80]	.079 -.098 [2.0 - 2.5]	CLEAR
SKK3035PT	.130 [3.30]	.098 -.118 [2.5 - 3.0]	COPPER
SKK3040PT	.150 [3.80]	.118 -.138 [3.0 - 3.5]	BLACK
SKK3045PT	.169 [4.30]	.138 -.157 [3.5 - 4.0]	CLEAR
SKK3050PT	.189 [4.80]	.157 -.177 [4.0 - 4.5]	COPPER
SKK3055PT	.209 [5.30]	.177 -.197 [4.5 - 5.0]	BLACK
SKK3060PT	.228 [5.80]	.197 -.217 [5.0 - 5.5]	CLEAR
SKK3065PT	.248 [6.30]	.217 -.236 [5.5 - 6.0]	COPPER

DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED	
DIMENSIONS IN INCH [MM]	METRIC
SPECIFIED ANGLES	$\pm 1/2^\circ$ INCH [±.020] METRIC
LINEAR DIM	XXX ± 0.5 X ± 0.3 XX ± 0.2 X ± 0.1 .XXX [±.005] [± 1/64]
FRACTIONS	
SURFACE ROUGHNESS	3.2/Ra 125
BREAK ALL EDGES R0.1-0.2 [0.005-.010] TOL. APPLY AFTER FINISH - DO NOT SCALE PRINT	
DRWN BY: GM	DATE: 6/25/2009
CHKD BY: GM	6/25/2009
APPR.:	
ECO NO.: 23283	RELEASED:
REF.: Z-4401	

This drawing and the subject matter thereon is the proprietary property of Emhart Technologies, a Black & Decker Co. and is to be treated by you as confidential, proprietary information. This drawing thereof shall not be duplicated or subject matter disclosed to others, for any purpose whatsoever, without the express written consent of Emhart Technologies and must be returned to Emhart Technologies. Copyright Emhart Technologies 2006	
MATERIAL	EMHART TECHNOLOGIES 50 SHELTON TECHNOLOGY CENTER SHELTON, CT. 06484 www.emhart.com Emhart Technologies A BLACK & DECKER COMPANY
BODY: SAE 1006 MANDREL CARBON STEEL	
HEAT TREAT	"POP" RIVET-OPEN END, COUNTERSUNK, STEEL, PULL-THRU, 3MM
N/A	
FINISH	SEE NOTE 5
SIZE	GLOBAL NO.
B	PART NO. SEE CHART
TYPE OR	DRAWING NO. SKK30-PT
SCALE	SHEET 1 OF 1
LOCATION HOP	REV D